

# QUALITY CERTIFICATION

HOSE: HYDRAULIC HOSE SAE100 R6 5/16" NORM: SAE J517 SAE 100 FIRM: ORDER NO.:	CODE: REPORT NO.: 2024T0914004 DATE OF TEST: 2024/09/13 DATE OF REPORT: 2024/09/14
---	---

TEST NMAE	SPECIFICATION	RESULT			METHOD	
		NO:1	NO:1	NO:1		
<b>1.0 DIMENSION CONTROL</b>					EN 24671	
1.1 Inside Diameter, mm	7.6-8.0	7.8	7.9	7.8		
1.2 Outside Diameter, mm	13.6-14.0	13.9	14	13.9		
1.3 Concentricity (internal-outside/diameter)	MAX:0.8	0.7	0.6	0.5		
1.4 Cover wall thickness mm	0.8-1.5	OK	OK	OK		
1.5 Inner compound	NBR	OK	OK	OK		
1.6 Inner compound code	6280	OK	OK	OK		
1.7 Cover compound	CR/NBR	OK	OK	OK		
1.8 Cover compound code	3345	OK	OK	OK		
<b>2.0 HYDROSTATIC TEST</b>					EN ISO 1402	
2.1 Working Pressure, MPA	2.8	OK	OK	OK		
2.2 Change Elongation at W.P. %	+2/-4	0.6	0.5	0.8		
2.3 Proof Pressure, MPA	5.6	OK	OK	OK		
2.4 Burst Pressure, MPA	MIN:11.2	12	13	12		
2.5 Minimum Bend Radius, (130mm) %	MAX:1.0	OK	OK	OK		
2.6 Working temp. MAX	(-40°C/+100°C)	OK	OK	OK		
<b>3.0 COLD FLEXIBILITY</b>					EN 24672/B	
3.1(-40°C/24h) (TUBE)	No Crack	Not Cracked	Not Cracked	Not Cracked		
3.2(-40°C/24h) (COVER)	No Crack	Not Cracked	Not Cracked	Not Cracked		
<b>4.0 ADHESIVE</b>					EN 28033	
4.1 Liner-Reinforcement, kgf/cm	MIN:2.5	No Separate	No Separate	No Separate		
4.2 Reinforcement - Cover, kgf/cm	MIN:2.5	No Separate	No Separate	No Separate		
<b>5.0 FIULD RESISTANCE</b>					ISO 1817	
5.1 ASTM NO:3 (CHANGE IN VOLUME)						
5.1.1(100°C.72h) (TUBE) %	0/100	8.25	8.25	8.25		
5.1.2(100°C.72h) (COVER) %	0/100	38.67	38.67	38.67		
<b>6.0 LEAKAGE TEST</b>					EN ISO 1402	
6.0 LEAKAGE TEST MPA	6	OK	OK	OK		
<b>7.0 OZONE RESITANCE</b>					EN 27326/1-2	
(40C/50 pphm O3/72h/%20 Elon./ 2X) (COVER)	Rating:0	Rating:0	Rating:0	Rating:0		
<b>8.0 VACUUM</b>					ISO 6803	
8.0 VACUUM bar	MAX:-0.8	OK	OK	OK		
<b>9.0 IMPULSE TEST</b>					ISO 6803	
9.0 IMPULSE TEST Cycles	MIN:200.000	OK	OK	OK		
OBERVATIONS:"THE SAMPLES TESTED WERE FROM TAKEN FROM HOSES WHICH WERE PRODUCED FOR						

INSPECTOR: SIGNATURE:	APPROVED: SIGNATURE
--------------------------	------------------------